



# EQ1-NX

## SINGLE LENGTH



Wishon's new single length iron design concept EQ1-NX offers same length and high COR low loft iron characteristics while adding many new performance enhancing features to mark a definite step forward in game improvement iron design.

### Features:

- Enabled by the new 2-piece hollow body design, the Center of Gravity moves progressively through the set from lowest and most rear located on the #5 iron to highest and most forward located on the GW and SW to achieve more consistent shot shape and shot height for each iron in the set
- The hollow body design throughout the set increases the MOI of each head by removing all mass from the inside of the head to be distributed all around the CG. The hollow body construction also enables the CG progression and uniform impact sound between the high COR and conventional COR heads in the set
- Low number irons are better matched with their loft to CG position to achieve preferred shot shape/height and allow a wider range of players to be able to effectively hit the #5 and 6 irons to fly and carry with proper distance gaps
- Traditional GW and SW profile shapes are combined with milled faces and a custom sole grind make the wedges a great choice even if they were standalone wedges and not part of the single length design
- 275g head weight with hosel weight bore allows assembly to any single length between 35.5" and 37.5" while still being able to achieve a reasonable range of swingweight/MOI (depending on shaft weight and grip weight)

Head	Desc	Loft	Lie	Weight	Offset	Sole Angle	Toe Height	Heel Height	Blade Length
TW866-5	5-iron	24°	63°	275g	2mm	5°	57mm	33mm	83mm
TW866-6	6-iron	28	63	275	2	5	57	33.5	83mm
TW866-7	7-iron	32	63	275	2	5	59	34	83mm
TW866-8	8-iron	36	63	275	2	5	60	35	83mm
TW866-9	9-iron	40	63	275	2	5	60.5	35.5	83mm
TW866-PW	PW	45	63	275	2	6	61	36	83mm
TW866-GW	GW	50	63	275	2	10	61	36	83mm
TW866-SW	SW	55	63	275	2	12	61.5	36.5	83mm



#### Head Material:

431 Stainless Steel (body); C455 HSS (#5, 6, 7 faces)

#### Ferrule Required:

Any IR ferrule with 13.2mm bottom OD and 0.370" ID (#121-IR)

#### Scorelines:

U-Groove 0.8mm wide x 2.8mm spacing x 0.4mm deep

#### Loft/Lie Bending:

+/-3° in any direction

#### Hosel Length/Bore Depth:

65mm/30mm

#### Hosel Weight Bore:

capacity. 9g

#### Sole Width Range Toe/Centre/Heel:

#5, 6 - 20.5mm/19.5mm/15mm; #7, 8 9, P - 21mm/20mm/15.5mm; GW - 22mm/21mm/17mm; SW - 23mm/22mm/17mm

#### Face-Back Sole Radius at Toe/Centre/Heel:

#5-PW - 50mm/45mm/40mm; GW-SW - Custom Grind

#### Bottom of Bore to Ground:

1 5/8" (40mm)



TONY@TSHGOLF.COM

WWW.TSHGOLF.COM